Serial No. 10/055,090 Amdt. dated August 26, 2004 Reply to Office Action dated June 10, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A method for measuring auditory evoked potentials of an auditory system of a patient or animal body, said comprising:

surgically implanting at least two pickup electrodes in the temporo-occipital area inside said body,
picking up electrical signals resulting from neuronal activity of said auditory system by means of said
at least two pickup electrodes, and
producing signals representative of neuronal activity of said auditory system from said electrical

2. (Previously Presented) The method according to claim 1 wherein said at least two extracochlear pickup electrodes are surgically implanted in the temporo-occipital area of said body, so that a line linking said pickup electrodes is substantially parallel to the cerebral trunk of said body.

signals sensed by said pickup electrodes.

- 3. (Previously Presented) The method according to claim 1 wherein said electrical signals have an amplitude between 0.1 μ V and 10 μ V.
- 4. (Previously Presented) The method according to claim 1 further comprising stimulating said auditory system by stimulation means implanted in said auditory system, thereby generating said neuronal activity of said auditory system.

Serial No. 10/055,090 Amdi: dated August 26, 2004 Reply to Office Action dated June 10, 2004

- (Previously Presented) The method according to claim 4 wherein said stimulation means are implanted in the cochlea of said auditory system.
- 6. (Previously Presented) The method according to claim 4 wherein said stimulation means are implanted outside of the cochlea of said auditory system.
- 7. (Previously Presented) The method according to claim 1 further comprising acoustically stimulating said auditory system by stimulation means implanted in said auditory system, thereby generating said neuronal activity of said auditory system.
- 8. (Previously Presented) The method according to claim 1 further comprising mechanically stimulating said auditory system by a vibrator implanted in said auditory system, thereby generating said neuronal activity of said auditory system.
- 9. (Previously Presented) The method according to claim 1 further comprising electrically stimulating said auditory system by at least one stimulation electrode implanted in said auditory system, thereby generating said neuronal activity of said auditory system.
- 10. (Previously Presented) The method according to claim 9 wherein said at least one stimulation electrode forms a stimulation dipole which is surgically implanted so as to be substantially perpendicular to a line linking said at least two pickup electrodes.

Serial No. 10/055,090 Amdt. dated August 26, 2004 Reply to Office Action dated June 10, 2004

- 11. (Previously Presented) The method as in claim 10 further comprising positioning said stimulation dipole with respect to said at least two pickup electrodes so as to reduce stimulation artifact in said electrical signals resulting from neuronal activity of said auditory system.
 - 12. (Previously Presented) The method according to claim 1 further comprising: surgically implanting a plurality of electrodes in the temporo-occipital area in said body, and selecting said at least two pickup electrodes and at least one stimulation electrode from said plurality of electrodes, based on quality of signals detected by said pickup electrodes.
- 13. (Previously Presented) The method according to claim 12 further comprising selecting a pickup reference electrode and a stimulation reference electrode from said plurality of electrodes.
- 14. (Previously Presented) The method according to claim 1 further comprising stimulating at least a portion of said auditory system by means of at least one surgically implanted vibrator.
- 15. (Previously Amended) The method as in claim 1 further comprising amplifying said electrical signals resulting from neuronal activity of said auditory system, and transmitting the amplified electrical signals through the skin of said body, and producing said signals representative of neuronal activity of said auditory system from said transmitted electrical signals.

Serial No. 10/055,090 Amdt. dated August 26, 2004 Reply to Office Action dated June 10, 2004

16. (Currently Amended) An implantable device for measuring auditory evoked potentials of an auditory system of a patient or animal body, said device comprising:

at least two extracochlear pickup electrodes implantable in a patient or animal temporo-occipital area inside said body for sensing electrical signals resulting from neuronal activity of the auditory system of said body, said sensed electrical signals having an amplitude on the order of 1 μV to 10 μV, and

an amplifier module having input terminals connected respectively to said extracochlear pickup electrodes, said amplifier module producing signals representative of neuronal activity of said auditory system from said electrical signals sensed by the extracochlear pickup electrodes.

- 17. (Previously Presented) The device according to claim 16 wherein said at least two extracochlear pickup electrodes are spaced apart by more than 3 cm.
- 18. (Previously Amended) The device according to claim 16 further comprising a sealed package containing said amplifier module, said extracochlear pickup electrodes being placed on either side of said sealed package in substantially diametrically opposite positions, and are mounted at the ends of a flexible support enabling them to be positioned optimally.
- 19. (Previously Presented) The device according to claim 16 comprising at least three extracochlear pickup electrodes implantable in a patient or animal body outside of the cochlea of said auditory system for sensing electrical signals resulting from neuronal activity of the auditory system of said body, a sealed package containing said amplifier module and a multiplexer, said at least three extracochlear pickup

Serial No. 10/055,090 Amdt. dated August 26, 2004 Reply to Office Action dated June 10, 2004

electrodes being connected to the amplifier module via said multiplexer and being placed so as to be distributed around the package on a flexible support.

- 20. (Previously Presented) The device according to claim 16 further comprising a sealed package containing said amplifier module, a pickup reference electrode, and means for moving said pickup reference electrode relative to said sealed package.
- 21. (Previously Amended) The device according to claim wherein said pickup reference electrode is fixed on said package.
- 22. (Previously Presented) The device according to claim 16 further comprising stimulation means for stimulating said auditory system, thereby generating said neuronal activity of said auditory system.
- 23. (Previously Presented) The device according to claim 22, wherein said stimulation means comprise at least one stimulation electrode for electrically stimulating at least a portion of said auditory system.
- 24. (Previously Presented) The device according to claim 23 wherein said at least one stimulation electrode forms a stimulation dipole which is disposed substantially perpendicularly to a line linking two of said pickup electrodes.

Serial No. 10/055,090 Amdt. dated August 26, 2004 Reply to Office Action dated June 10, 2004

- 25. (Previously Presented) The device according to claim 24 further comprising means for positioning said at least two extracochlear pickup electrodes with respect to said stimulation dipole so as to reduce stimulation artifacts.
- 26. (Previously Presented) The device according to claim 22, wherein said stimulation means comprise acoustic stimulation means for stimulating at least a portion of said auditory system.
- 27. (Previously Presented) The device according to claim 22, wherein said stimulation means comprise at least one vibrator for mechanically stimulating at least a portion of said auditory system.
- 28. (Previously Amended) The device according to claim 16 wherein said amplifier module comprises a differential amplifier connected to said two extracochlear pickup electrodes and having a ground terminal connected to a reference pickup electrode implantable of the mastoid of said body.
- 29. (Previously Presented) The device according to claim 16 further comprising a reference pickup electrode implantable on the mastoid of said body, said amplifier module having one ground terminal connected to said reference pickup electrode.
- 30. (Previously Presented) The device according to claim 16 wherein said amplifier module comprises means for amplifying signals having an amplitude 100 to 1000 times smaller than the amplitude of signals detected with electrodes placed in the cochlea of said auditory system, for producing signals representative

Serial No. 10/055,090 Arndt. dated August 26, 2004 Reply to Office Action dated June 10, 2004

of neuronal activity of said auditory system from said electrical signals sensed by the extracochlear pickup electrodes.

- 31. (Previously Presented) The device according to claim 16 further comprising a signal processor for processing said signals representative of said neuronal activity.
- 32. (Previously Presented) The device according to claim 16 further comprising a sealed package containing said amplifier module and a transmitter for transmitting radio signals through the skin of said body.